

PORCELAIN VENEER PERFORMANCE DATA

PHYSICAL PROPERTIES	TEST ASTM	STANDARD A137.1	RESULTS
Water absorption *	C373	≤ 0.5%	COMPLY WITH ANSI A137.1
DCOF Average dynamic coefficient of friction **	ANSI A.326.3	As reported	NOT APPLICABLE
Skid Resistance	DIN 51097	NOT APPLICABLE	NOT APPLICABLE
	DIN 51130		
Resistance to freeze/thaw cycling *	C1026	As reported	RESISTANT
Resistance to thermal shock	C484	As reported	RESISTANT
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	COMPLY WITH ANSI A137.1
Warpage (edge) Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	COMPLY WITH ANSI A137.1
Wedging Chemical resistance	C502	± 0.25% or ± 0.03 in	COMPLY WITH ANSI A137.1
Chemical resistance	C650	As reported	UNAFFECTED
Resistance to stain	C1378	As reported	UNAFFECTED
Thickness	C499	Range: 0.04 in	COMPLY WITH ANSI A137.1
Breaking strength	C648	250 lbf or greater	COMPLY WITH ANSI A137.1

- Average values referred to our production and related to the matt finish of the product. - Be sure to use porcelain veneers belonging to the same caliber.
- Test results are available on request.
- The information provided can be subject to change. Please refer to **outdoor.landmarkceramics.com** for the latest, most accurate and up-to-date information.



























Nominal Size: 5.8"x24"Nominal Size: 20.5"x5.8"x2.75"

The color of porcelain veneers printed in this catalog may differ from actual veneers. Tile color reproductions in this catalog are representative only. Slight tone and shade variations are inherent in porcelain veneers. Before selecting a color, we recommend that you contact your local representative, who will provide you with a sample piece of the requested porcelain veneer.

This porcelain veneer product is manufactured with a V2 shade variation. Remember that the amount of color as well as the texture of each piece may vary from piece to piece. Inspect the product immediately upon delivery and select pieces from many boxes during installation to minimize and blend any possible color difference.



SMOKE

BLUESTONE BLUE SELECT

QUARRY LEDGEST



CORNER •• SMART CORNER ••

RECOMMENDED USE

Veneer World is recommended for indoor and outdoor walls in commercial and residential application. Landmark recommends an offset no greater than 30%, if a staggered pattern is required for tiles of 20" inches or longer.

CARE AND MAINTENANCE

Do not apply any wax or sealer to the product after installation. Regular cleaning is the best way to keep porcelain veneers looking good.

Use clean, hot water (add household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots.

Please visit outdoor, landmark ceramics, com for further information regarding the care and maintenance of Landmark products.

Landmark guarantees that its products will meet or exceed the performance specifications set out in ANSI A137.1-2012 and in the performance specifications section of the Landmark general catalog. For more information, please visit our website at outdoor.landmarkceramics.com.

BLUESTONE FULL COLOR



INFORMATION









LEARN MORE ABOUT



