

PHYSICAL PROPERTIES	TEST ASTM	STANDARD A137.1*	RESULTS
Water absorption *	C373	≤ 0.5%	COMPLY WITH ANSI A137.1
DCOF Average dynamic coefficient of friction **	ANSI A.326.3	As reported	NOT APPLICABLE
Skid Resistance	DIN 51097	NOT APPLICABLE	NOT APPLICABLE
	DIN 51130		
Resistance to freeze/thaw cycling *	C1026	As reported	RESISTANT
Resistance to thermal shock	C484	As reported	RESISTANT
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	COMPLY WITH ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	COMPLY WITH ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	COMPLY WITH ANSI A137.1
Chemical resistance	C650	As reported	UNAFFECTED
Resistance to stain	C1378	As reported	UNAFFECTED
Thickness	C499	Range: 0.04 in	COMPLY WITH ANSI A137.1
Breaking strength	C648	250 lbf or greater	COMPLY WITH ANSI A137.1

* Average values referred to our production and related to the matt finish of the product.
 ** As far as values relating to the matt finish of the product and to tests carried out by certified external laboratories whose results are available upon request at Headoffice, we are willing to check the lot you are interested in purchasing.
 - Be sure to use tiles belonging to the same caliber.
 - Test results are available on request.
 - The information provided can be subject to change. Please refer to lcsa.com for the latest, most accurate and up-to-date information.

February 2026 - © Landmark Ceramics

LEARN MORE ABOUT

ICUSA.COM

LANDMARK CERAMICS

CERTIFIED PORCELAIN
 VOC FREE
 USGBC MEMBER
 Member of CERAMIC
 Declare.
 GREEN SOURCE
 INTERNATIONAL WELL-BEING BUILDING SYSTEMS
 EPD
 npdc

ATELIER GROOVE S

INDIANA BUFF SELECT
12"x24" ±0.35" / 9 mm

ATELIER DYNAMIC

INDIANA GREY SELECT
12"x24" ±0.35" / 9 mm

ATELIER WAVE

INDIANA BUFF SELECT
12"x24" ±0.35" / 9 mm

ATELIER BAMBOO

TRAIL VEIN CUT PEARL
12"x24" ±0.35" / 9 mm

ATELIER GROOVE S

INDIANA GREY SELECT
12"x24" ±0.35" / 9 mm

ATELIER DYNAMIC

INDIANA BUFF SELECT
12"x24" ±0.35" / 9 mm

ATELIER COMBED

ESSENCE MONTAUK WHITE
12"x24" ±0.35" / 9 mm

ATELIER BAMBOO

TRAIL VEIN CUT GREY
12"x24" ±0.35" / 9 mm

ATELIER WAVE

INDIANA BUFF SELECT
12"x24" ±0.35" / 9 mm

ATELIER COMBED

INFINITY SKY
12"x24" ±0.35" / 9 mm

ATELIER BAMBOO

ESSENCE MONTAUK GREY
12"x24" ±0.35" / 9 mm **10%**

ATELIER BAMBOO

TRAIL VEIN CUT BEIGE
12"x24" ±0.35" / 9 mm

ATELIER GROOVE L

INDIANA GREY SELECT
12"x24" ±0.35" / 9 mm

ATELIER WAVE

INFINITY DESERT
12"x24" ±0.35" / 9 mm

ATELIER COMBED

ESSENCE MONTAUK BLACK
12"x24" ±0.35" / 9 mm **10%**



INFORMATION

RECOMMENDED USE
 Veneer World is recommended for indoor and outdoor walls in commercial and residential application. Landmark recommends an offset no greater than 30%, if a staggered pattern is required for tiles of 20" inches or longer.

CARE AND MAINTENANCE
 Do not apply any wax or sealer to the product after installation. Regular cleaning is the best way to keep porcelain veneers looking good. Use clean, hot water (add household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. Please visit outdoor.landmarkceramics.com for further information regarding the care and maintenance of Landmark products.

WARRANTY
 Landmark guarantees that its products will meet or exceed the performance specifications set out in ANSI A137.1-2012 and in the performance specifications section of the Landmark general catalog. For more information, please visit our website at outdoor.landmarkceramics.com.

Color Shading

V1 UNIFORM APPEARANCE	V2 SLIGHT VARIATION	V3 MODERATE VARIATION	V4 SUBSTANTIAL VARIATION
--------------------------	------------------------	--------------------------	-----------------------------

